



Color :

White

UPC Code: 078477819425

Country Of Origin: Please Contact Customer

Service.

RoHS Compliant: Yes

NEMA : 5-15R

Available Colors:







Brown

Gray

lvory

16262-W

Decora Plus Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings
At Rated Voltage: 1/2 HP

Electrical Specifications

Amperage: 15 A

Current Limiting : Full Rated Current **Dielectric Voltage :** Withstands 2000V

per UL498

Grounding: Self-Grounding

Pole: 2

Temperature Rise: Max 30C at 250 cycles OL at 200 pct rated current

Voltage: 125 VAC

Wire: 3

Environmental Specifications

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 60°C

Material Specifications

Body Material: Thermoplastic Nylon **Clamp Nuts**: Zinc-Plated Steel

Color: White

Face Material: Thermoplastic Nylon Ground Clips: Brass-Plated Grounding Screw: Brass 8-32

Line Contacts: Brass Triple-Wipe .031 Thick

Strap Material: Zinc-Plated Steel **Terminal Screws**: Brass 10-32

Mechanical Specifications

Product ID: Ratings are permanently

marked on device

Screw Terminal Torque: 14-18 in-lbs

Terminal Accom.: 14-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Termination: Back or Side Wire

Product Features

Brand : Decora Plus

Color : White

Device Type : Duplex Receptacle Outlet

Feature 4 : Smooth Face **Grade :** Heavy-Duty Industrial Specification Grade

NEMA: 5-15R

Standards and Certifications


ANSI: C-73

CSA C22.2 No. 42 : File 152105

NEMA: WD-6 **NOM**: 057

UL498: File E13399 **Warranty**: 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

